

Kilsaran Cemfloor



Cemfloor has a multitude of installation & performance benefits:

- No sanding or Priming required for adhesives - Floor coverings can be applied directly to Cemfloor
- Self-Levelling - Ease of Installation up to 1000m² per day
- Self-Compacting - No Voids
- From 35mm (55mm Underfloor Heating) and up to 100mm depth
- Up to 150m² (100m² underfloor heating) without joints
- Minimal Dry Shrinkage (<0.05%)
- Foot traffic after 24 hours
- Can be force dried by commissioning underfloor heating after 1 week
- Thermal performance that maximises heat transfer from heating system
- Ideal for use in wet areas and wet rooms
- Computerised production to ensure highest level of product consistently
- Due to the technical nature of Cemfloor preparation and installation, we supply Cemfloor through a network of approved installers.

Our dedicated screed production facility, based in Killeen Road, Dublin 12 operates Monday to Saturday.

To find out more visit www.kilsaran.ie/product/cemfloor

Kilsaran Cemfloor is an innovative, high-performance, cement based liquid screed which complies with EN 13813.

All Cemfloor screeds are delivered to site ready for use, ensuring consistent quality from project to project.

Cemfloor levelling screed is ideal for both commercial & residential projects as well as smaller domestic projects due to its speed of installation and reduced installation time. The high thermal performance of Cemfloor means it is ideal for use with under floor heating.

