



Kilsaran

KPRO
FLOOR

Introducing our New LevelEase Range Your Complete Flooring Solution



LevelEase 250

A rapid hardening and fibre reinforced cementitious levelling compound for use in domestic and commercial applications, over a multitude of substrate. Laying depth 2mm-50mm. CT-C30-F7.



LevelEase 225

A standard-setting and fibre-reinforced cementitious levelling compound for use in domestic and commercial applications. Laying depth 2mm-25mm. CT-C25-F6.



LevelEase Duo 225

A standard-setting two component cementitious levelling compound for use in domestic and commercial applications. Laying depth 2mm-25mm. CT-C25-F6.



LevelEase 110

A rapid hardening self levelling compound designed for smoothing uneven floors before installing final floor coverings. Ideal for both domestic and commercial projects, it creates a smooth, level surface from 0-10mm on concrete and screeded substrates.



LevelEase Sealing Primer

A high-performance, deep-penetrating primer designed to strengthen absorbent substrates and improve adhesion for subsequent layers. It ensures reduced absorbency and enhanced workability for a wide range of surface preparation tasks.



LevelEase Gritty Primer

A quartz infused, high-performance and fast-setting bonding primer which delivers a textured, gritty finish that significantly enhances the adhesion of subsequent layers, to smooth non-absorbent substrates.



LevelEase DPM

A one-component, water-based residual moisture vapor suppressant, designed to suppress residual construction moisture in cementitious substrates, where the moisture content is up to 95% RH.

Get in touch:

ROI: T: 01 801 3484 www.kilsaran.ie | UK: T: 0161 872 8899 www.kilsaraninternational.co.uk

Place an Order: orders@kilsaran.ie Customer Service: csteam@kilsaran.ie

Tech Support: techsupport@kilsaran.ie





Kilsaran

KPRO FLOOR



		LevelEase 110	LevelEase 225	LevelEase Duo 225	LevelEase 250
Laying Dept		0mm – 10mm	2mm – 25mm	2mm – 25mm	2mm – 50mm
Suitability of substrates	Concrete	...	..	..	...
	Plywood*	o	o	o	...
	S&C Screed	...	..	..	...
	Calcium Sulphate Screed	...	..	..	...
	Ceramic Tiles	o	..	..	...
Substrate preparation	LevelEase Sealing Primer	Required	Required	Required	Required
	LevelEase Gritty Primer	Required on tiled substrates	Required on tiled substrates	Required on tiled substrates	Required on tiled substrates
	LevelEase DPM	If substrate moisture is $\geq 75\%$ RH, $\leq 95\%$ RH	If substrate moisture is $\geq 75\%$ RH, $\leq 95\%$ RH	If substrate moisture is $\geq 75\%$ RH, $\leq 95\%$ RH	If substrate moisture is $\geq 75\%$ RH, $\leq 95\%$ RH
Open to foot traffic		2-4 hours	2-4 hours	2-4 hours	2-4 hours
Installation of floor coverings	Tiles		12 hours	12 hours	6 hours
	Resilient Coverings	24 hours	24 hours	24 hours	24 hours

* Suitability of Substrates: ... Ideal .. Suitable o Not Suitable

Get in touch:

ROI: T: 01 801 3484 www.kilsaran.ie | UK: T: 0161 872 8899 www.kilsaraninternational.co.uk

Place an Order: orders@kilsaran.ie Customer Service: csteam@kilsaran.ie

Tech Support: techsupport@kilsaran.ie

